

Product data sheet

PTECD L20 & PTECD R * OP
PROTEC LED
DEXTRA




IP
20



Protec LED - Ø174mm, IP20 Recessed downlighter with ABS housing and bezel, zinc plated spring steel fixing clips, anodised aluminium reflectors. LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest Emergency Lumen Values: No Coloured Ring: Opti-Spec: 367, Opti-Sat: 357 Drop Glass Ring: Opti-Spec: 344, Opti-Sat: 335 IP44 Cover: Opti-Spec: 343, Opti-Sat: 333 Microprism Diffuser: Opti-Spec: 274, Opti-Sat: 263 Opal Diffuser: Opti-Spec: 262, Opti-Sat: 243 S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* Replace * with WH for white ring or GY for Grey

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	16.5 W	CRI	80
Total flux	1377 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	16.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.84 in
Diameter: 6.89 in

Adjustability

Fixed

Electric

System power: 16.5 W
Ballast: ECG

Protection

IP: 20
Designation labels: CE