


Product data sheet

PLACE 28W 3000K RA>80 CD GREY
8246087999
SG ARMATUREN



Place is an all-round post-top luminaire with a unique, aesthetic design. The soft transition from the pole to the large surface gives a unique expression. Place combines visual comfort and energy efficiency for a variety of urban environments, such as parks, car parks and other public areas. An obvious choice for many kinds of urban environments at an attractive price level. Ideal for retrofitted applications – luminaires easily mounted on existing poles. Designed for comfort, based on even light distribution. No light pollution. Design: Christian Hvidt. Light distribution: Direct - soft. Light source: LED 28W 3000K or 4000K Ra>80 SDCM:3. Control gear: On/Off Lumistep LS8 DYNADIM Philips Riegens Pr.2 Sweden. Protection Class II, IP66, Ta=25°C, CE, IK10. Optics: Direct symmetric opal. Materials and Finish: Housing/base: Die-cast aluminium, anodised, powder coated, textured grey or black. Gear tray in special anticorrosive aluminium. Optic in vacuum formed PMMA - Outer optic in PC. Mounting/Connection Posts: For mounting onto 60mm or design pole. (Poles to be ordered separately). The luminaire is pre-wired with 6.0m cable. The control gear and LED is mounted onto a gear tray. Wind projected area 775 cm² - Max 7 kg. Surge Protection: Integrated Surge Protection (min. 4 kV). Extra surge protection for lightning strikes on request. Dimmable driver and other options on request. How to specify: Post or wall mounted (600mm diameter) IP66 rated LED luminaire. Base and top in die-cast aluminium, inner diffuser in PMMA opal and outer cover in polycarbonate (PC). Base and top shade finished in textured grey or black. Complete with control gear to operate LEDs, mounted onto a gear tray with plug/socket arrangement and pre-wired with power feed cable (6m). Post prepared for mounting onto 60mm or design pole. Protection Class II. As Riegens Place range.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	2370 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	28 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 11.33 in

Adjustability

Fixed

Electric

System power: 28 W
Appliance Class: II

Protection

IP: 66
IK: 10