Product data sheet


CALUMMA M MC RGBW 90°X15°
400
ANOLIS



IP 67 IK 10

Featuring an optical design using 7 high efficacy multi-chip LEDs and available with optional LED colour variants and various beam angles, the medium-sized Calumma M MC luminaire creates powerful and beautiful light output for a spot, accent or flood lighting solution. Its durable hou¬sing is built to withstand any exterior conditions, and its special finish for harsh and marine environments provides an exceptional outdoor LED luminaire in an elegant design. Additionally, Calumma M MC can be connected in long In/Out daisy-chains via an E-Box and hybrid Plug & Play connections for almost effortless installation. Complemented by wide range of accessories and control protocols, this luminaire is an effective and versatile unit to get the most out of architectural lighting applications.

Light output 1



1 x LED

Nominal lamp power	65 W	LOR	100%
Lamp flux	2109 lm	Total flux	2109 lm
Luminous efficacy	32 lm/W	Total power	65 W
CCT	6500 K		
CRI	79		

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Height: 10.94 in
Diameter: 9.29 in

Adjustability

Tiltable

Electric

System power: 65 W
Appliance Class: I

Protection

IP: 67
IK: 10