


Product data sheet

GUSTAV III (W. SHIELD ON SIDE FACING BUILDING)
9.683.5547.27
LEIPZIGER LEUCHTEN



Suitable for mounting heights from 3 metres to 4.50 metres, for medium lighting requirements. - Luminaire glazing made of UV-stabilised impact resistant clear polycarbonate - Extra glazing above the reflector - Special mirror disc reflector system made of highest grade aluminium, polished and anodised in order to direct the light and to protect against glare - Reflector Ø 630 mm made of aluminium with special white powder coating for excellent reflection - Cap made of aluminium - Base made of corrosion-resistant cast aluminium - One gear tray includes all electrical components - Simple connection with adapter jack - Luminaire available in any RAL or DB colour as required - Special pole Ø 76 mm for single and two brackets, please order separately (full range of poles see page 360 ff)

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	42 W	LOR	50%
Lamp flux	3200 lm	ULOR	10%
Luminous efficacy	34 lm/W	Total flux	1586 lm
CCT	2899 K	Total power	46 W
CRI	90		

Mounting mode

Pole top mounted

Electric

System power: 46 W

Shape and measurements

Height: 26.77 in
Diameter: 24.80 in