Product data sheet

CLARA IV (CLEAR ATTACHMENT) 9.764.3042.05


LEIPZIGER LEUCHTEN





For medium/high light requirements, mounting height 4.00 – 5.00 m. - Impact-resistant clear/opal polycarbonate attachment, UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order post dia.76mm separately (see standard poles from p. 258) -With adapter for concrete pole consisting of flange plate made of hot galvanized steel, and transition piece made of corrosionresistant cast aluminium

Light output 1



| 1 x High pressure mercury | vapour lamp |
|---------------------------|-------------|
| Nominal lamp power | 80 W |
| Lamp flux | 4000 lm |
| Luminous efficacy | 24 lm/W |
| CCT | 3400 K |
| CRI | 54 |

| LOR | 53% |
|-------------|---------|
| ULOR | 11% |
| Total flux | 2135 lm |
| Total power | 89 W |
| | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 22.83 in Diameter: 29.53 in Electric

System power: 89 W