Product data sheet

UNI-BRIGHT MOON SENSOR 180 CCT - 2700K/3000K/4000K MN18014WBSCCT

PROLED (MBN GMBH)









Multi-purpose mounted LED light with built-in motion detector and light sensor. Very suitable for staircases, storage rooms, garages or basements.

Light output 1



1 x LED	
Nominal lamp power	14 W
Lamp flux	1300 lm
Luminous efficacy	93 lm/W
CCT	4000 K
CRI	80

LOR	1009
Total flux	1300 ln
Total power	14 V




Nominal lamp power	14 W
Lamp flux	1300 lm
Luminous efficacy	93 lm/W
CCT	2700 K

1 x LED

CRI

LOR	100%
Total flux	1300 lm
Total power	14 W



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	1200 lm	Total flux	1200 lm
Luminous efficacy	86 lm/W	Total power	14 W
CCT	3000 K		
CRI	80		

80

Mounting mode

Ceiling mounted

Electric

System power: 14 W Appliance Class: I

Shape and measurements

Height: 1.38 in Diameter: 7.09 in Weight: 0.8 kg

Adjustability

Fixed

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

Protection

IP: 54

Other operating numbers

Ambient temperature range: 14...113°F