Product data sheet


MIRAGE 3 79
NARROW BLACK
WHITECROFT



IP 44


See lamps to select output and colur variants MIRAGE 3 recessed downlighter white reflector, narrow distribution. Narrow 11mm width bezel and shallow depth body. Graphite heat sink for optimum thermal management and superior optics designed for maximum visual comfort. Simple spring ceiling retention method to suit ceiling thicknesses between 1-40mm. Supplied with connected remote driver. Small round version, 79mm diameter cut out, 87mm over bezel. Emergency Output:- 6.3w - 56% 9.4w - 37%

Light output 1




1 x LED

Nominal lamp power	6.3 W	LOR	100%
Lamp flux	429 lm	ULOR	13%
Luminous efficacy	68 lm/W	Total flux	429 lm
CCT	4000 K	Total power	6.3 W
CRI	90		




1 x LED

Nominal lamp power	9.4 W	LOR	100%
Lamp flux	649 lm	ULOR	13%
Luminous efficacy	69 lm/W	Total flux	649 lm
CCT	4000 K	Total power	9.4 W
CRI	90		




1 x LED

Nominal lamp power	6.3 W	LOR	100%
Lamp flux	398 lm	ULOR	13%
Luminous efficacy	63 lm/W	Total flux	398 lm
CCT	3000 K	Total power	6.3 W
CRI	90		




1 x LED

Nominal lamp power	9.4 W	LOR	100%
Lamp flux	602 lm	ULOR	13%
Luminous efficacy	64 lm/W	Total flux	602 lm
CCT	3000 K	Total power	9.4 W
CRI	90		




1 x LED

Nominal lamp power	6.3 W	LOR	100%
Lamp flux	481 lm	ULOR	13%
Luminous efficacy	76 lm/W	Total flux	481 lm
CCT	3000 K	Total power	6.3 W
CRI	80		




1 x LED

Nominal lamp power	9.4 W	LOR	100%
Lamp flux	727 lm	ULOR	13%
Luminous efficacy	77 lm/W	Total flux	727 lm
CCT	3000 K	Total power	9.4 W
CRI	80		



1 x LED

Nominal lamp power	6.3 W	LOR	100%
Lamp flux	517 lm	ULOR	13%
Luminous efficacy	82 lm/W	Total flux	517 lm
CCT	4000 K	Total power	6.3 W
CRI	80		



1 x LED

Nominal lamp power	9.4 W	LOR	100%
Lamp flux	782 lm	ULOR	13%
Luminous efficacy	83 lm/W	Total flux	782 lm
CCT	4000 K	Total power	9.4 W
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in

Diameter: 3.35 in

Electric

System power: 6.3-9.4 W

Protection

IP: 44

Adjustability

Fixed