


Product data sheet

LUMINAIRES FOR EDUCATIONAL FACILITIES
V1-E0-00170-01OPA-4001640 E170 2.0 IP40 (595X180 MM) 16W OPAL EM 1H
VARTON




IP
40

IK
02

Luminaire for lighting pre-school, school, secondary, tertiary and other Educational facilities facilities. Meets all educational lighting requirements and standards. Stainless steel housing with white powder coating. Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: YXЛ4 Color rendering index: 90-100 Protection class: I Mounting method: Surface mounting/recessed mounting Ingress protection (IP): IP40 Radiation angle: 120 Impact resistance: IK02 Power factor: 0,95
https://www.varton.ru/products/svetilniki-dlya-obrazovatelnykh-uchrezhdeniy/e-seriya-2-0-dlya-klassov/e170-2-0-ip40-shkola-595kh180-mm-analog-2-18/svetodiodnyy-svetilnik-var-ton-e170-2-0-dlya-obrazovatelnykh-uchrezhdeniy-16-vt-cri90-vstraivaemyy-na_1/

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1680 lm	Total flux	1680 lm
Luminous efficacy	105 lm/W	Total power	16 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Electric

System power: 16 W

Shape and measurements

Length: 23.43 in

Width: 7.09 in

Height: 1.97 in

Protection

IP: 40

IK: 02

Adjustability

Fixed