Product data sheet


MIRAGE 3 110
MEDIUM WHITE
WHITECROFT



IP 44


See lamps to select output and colur variants MIRAGE 3 recessed downlighter white reflector, Medium distribution. Narrow 11mm width bezel and shallow depth body. Graphite heat sink for optimum thermal management and superior optics designed for maximum visual comfort. Simple spring ceiling retention method to suit ceiling thicknesses between 1-50mm. Supplied with connected remote driver. Medium round version, 110mm diameter cut out, 118mm over bezel. Emergency Output:- 8.4w - 41% 16.6w - 21% 26.5w - 11%

Light output 1




1 x LED

Nominal lamp power	16.6 W	LOR	100%
Lamp flux	2050 lm	ULOR	13%
Luminous efficacy	123 lm/W	Total flux	2050 lm
CCT	4000 K	Total power	16.6 W
CRI	80		




1 x LED

Nominal lamp power	26.5 W	LOR	100%
Lamp flux	3179 lm	ULOR	13%
Luminous efficacy	120 lm/W	Total flux	3179 lm
CCT	4000 K	Total power	26.5 W
CRI	80		




1 x LED

Nominal lamp power	8.4 W	LOR	100%
Lamp flux	796 lm	ULOR	13%
Luminous efficacy	95 lm/W	Total flux	796 lm
CCT	3000 K	Total power	8.4 W
CRI	90		




1 x LED

Nominal lamp power	16.6 W	LOR	100%
Lamp flux	1579 lm	ULOR	13%
Luminous efficacy	95 lm/W	Total flux	1579 lm
CCT	3000 K	Total power	16.6 W
CRI	90		




1 x LED

Nominal lamp power	26.5 W	LOR	100%
Lamp flux	2448 lm	ULOR	13%
Luminous efficacy	92 lm/W	Total flux	2448 lm
CCT	3000 K	Total power	26.5 W
CRI	90		




1 x LED

Nominal lamp power	8.4 W	LOR	100%
Lamp flux	858 lm	ULOR	13%
Luminous efficacy	102 lm/W	Total flux	858 lm
CCT	4000 K	Total power	8.4 W
CRI	90		




1 x LED

Nominal lamp power	26.5 W	LOR	100%
Lamp flux	2956 lm	ULOR	13%
Luminous efficacy	112 lm/W	Total flux	2956 lm
CCT	3000 K	Total power	26.5 W
CRI	80		




1 x LED

Nominal lamp power	16.6 W	LOR	100%
Lamp flux	1702 lm	ULOR	13%
Luminous efficacy	103 lm/W	Total flux	1702 lm
CCT	4000 K	Total power	16.6 W
CRI	90		




1 x LED

Nominal lamp power	26.5 W	LOR	100%
Lamp flux	2639 lm	ULOR	13%
Luminous efficacy	100 lm/W	Total flux	2639 lm
CCT	4000 K	Total power	26.5 W
CRI	90		




1 x LED

Nominal lamp power	8.4 W	LOR	100%
Lamp flux	1034 lm	ULOR	13%
Luminous efficacy	123 lm/W	Total flux	1034 lm
CCT	4000 K	Total power	8.4 W
CRI	80		



1 x LED

Nominal lamp power	8.4 W	LOR	100%
Lamp flux	941 lm	ULOR	13%
Luminous efficacy	112 lm/W	Total flux	941 lm
CCT	3000 K	Total power	8.4 W
CRI	80		



1 x LED

Nominal lamp power	16.6 W	LOR	100%
Lamp flux	1907 lm	ULOR	13%
Luminous efficacy	115 lm/W	Total flux	1907 lm
CCT	3000 K	Total power	16.6 W
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in

Diameter: 4.72 in

Adjustability

Fixed

Electric

System power: 8.4-26.5 W

Protection

IP: 44