

Product data sheet

TRIONA ROUND P
312362.002.1.76
RZB




IP
20

IK
03

Series: TRIONA round Decorative round LED pendant-mounted surface luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Canopy made of aluminium, powder-coated. Light emission through a diffuser in plastic, opal/prismatic. Lightguide and diffuser made of non-yellowing plastic (PMMA). Lateral light emission (RZB SIDELITE technology) for above-average homogeneous light distribution. 3-point steel cable suspension, steplessly adjustable. Easy installation with transparent, adjustable pendant cable and canopy with magnetic fixing. Driver integrated. Perfect for office areas (RUG < 19) and environments with computer screens in accordance with EN 12464-1. Colour: traffic white, matt (RAL 9016) Diameter: 1009 mm Height: 52 mm Suspension length: 500-1200 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 84 W Rated luminous flux: 9750 lm Beam angle Down: 95° Luminous efficacy: 116 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	84 W	CRI	80
Total flux	9750 lm	LOR	74%
Luminous efficacy	116 lm/W	ULOR	20%
		Total power	84 W

Mounting mode

Pendant

Shape and measurements

Height: 2.05 in
Diameter: 39.72 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 84 W

Protection

IP: 20
IK: 03