


Product data sheet

FACT-CO LED4100-840 3GU FL BKM
60714350
ZUMTOBEL



LED spotlight with stabilised colour temperature "Essential stableWhite"; optimised for efficient accent lighting in shops and showrooms; innovative thermal management employing passive cooling achieves COOL TOUCH function; Luminaire with 3-phase universal adapter Global GA69 (for Zumtobel 3-phase/L3+DALI track), ; lamp(s): 1/36W LED4100-840; Colour rendering Ra > 80, colour temperature 4000 K (neutral white); Luminaire or spotlight with FLOOD light distribution; Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 4100 lm, Luminaire efficacy: 114 lm/W; service life: 50000 h for luminous flux at 80% of initial value; UVA-free and IR-free light; total power: 36 W; mains voltage: 220-240V/ 50/60Hz; spotlight can rotate through 360° and tilt through 90°; spotlight housing made of die-cast aluminium, surface finish: microtextured paint in black; electronic control gear fitted in spotlight housing; specular reflector made of polycarbonate highly reflective aluminized finish, iridescence-free; dimensions: 220x115x195 mm; weight: 1.2 kg; Note: Wall mounting is not permissible with the adapter version, the point outlet is only suitable for ceiling mounting!

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	4100 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	36 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 8.66 in
Width: 4.53 in
Height: 7.68 in
Weight: 1.2 kg

Design

Material impression: Aluminum
Color of housing: Black

Electric

System power: 36 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE