



# Product data sheet

MATRIC 38MM WALL DIRECT-INDIRECT - W1  
LW1BEE-840H-L600  
LIGHTNET



LED wall mounted luminaire. Direct-indirect light distribution. Light channel made of aluminium profile with 38mm track width. Precise length production according to specifications possible. Surface natural anodised or white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Opal diffuser made of acrylic glass for general lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial  $\leq$  MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27 W	CRI	82
Total flux	2920 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	54%
		Total power	27 W

## Mounting mode

Wall mounted

## Electric

System power: 27 W

## Shape and measurements

Length: 23.62 in

Width: 2.95 in

Height: 2.95 in

## Protection

## Adjustability

Fixed