


# Product data sheet

CIRQUA-L 1X2600-930 F-DA  
0331976AH  
RIDI



Spotlight Design: Spotlight LED in a modern design for lighting track mounting. Conical reflector housing dia. 100 mm in die-cast aluminium with internal cooling fins for maintenance-free passive cooling. Reflector housing linked by a swivel-and-tilt fixture to a die-cast aluminium device housing with built-in LED driver. Surface powder-coated in white (similar to RAL 9016) and black (FSW; similar to RAL 9005). Specular reflector made of pure aluminium. Clear protective glass normally pre-fitted. Reflector housing closing ring made of plastic. Reflector housing can be rotated by 350° with a 90° swivel action. Pre-fitted COB LED module. Frame trim made from die-cast aluminium, attached by magnetic connection, ensures a seamless transition between the lighting track and device housing. Colour rendering in index Ra  $\geq$  80 or Ra  $\geq$  90, colour temperature 3000 Kelvin (830), 4000 Kelvin (840), or 3000 Kelvin (930). Protection rating IP20, protection class I. Colour rendering in index Ra  $\geq$  80 or Ra  $\geq$  80, colour temperature 3000 Kelvin (830/930), 4000 Kelvin (840). Electronic DALI converter for LED, 220-240 Volt, 0/50-60 Hz and three phase trunking adapter with phase selection + DALI. Mounting: Mounted using three-phase adapter on the lighting track. CIRQUA-L ...F... Specular reflector made of pure aluminium. 36° flood reflector beam angle.

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 26 W    | CRI         | 90     |
| Total flux         | 2510 lm | LOR         | 79%    |
| Luminous efficacy  | 97 lm/W | ULOR        | 4%     |
|                    |         | Total power | 26 W   |

## Mounting mode

Pendant, Contact rail

## Shape and measurements

Length: 12.20 in  
Width: 2.28 in  
Height: 3.90 in

## Adjustability

Rotatable, Tilttable

## Design

Color of housing: Black, White

## Electric

System power: 26 W  
Appliance Class: I

## Protection

IP: 20