


Product data sheet

GATU 21-001W-10GJV/930, B
21-001W-10GJV/930
HALLA




21-001W-10GJV/930, B Luminaire recessed Material of luminaire: Colour of luminaire: Shape of luminaire: Angular Size: 185 x 185 x 120 mm
Type of installation: Recessed Distribution: Direct Optics type: Reflector Protection class: II Voltage: 220-240V


Light output 1




1 x LED			
Nominal lamp power	42 W	LOR	100%
Lamp flux	3490 lm	Total flux	3490 lm
Luminous efficacy	83 lm/W	Total power	42 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	13.8 W	LOR	100%
Lamp flux	1440 lm	Total flux	1440 lm
Luminous efficacy	104 lm/W	Total power	13.8 W
CCT	3000 K		
CRI	90		




1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1790 lm	Total flux	1790 lm
Luminous efficacy	99 lm/W	Total power	18 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	20.1 W
Lamp flux	1950 lm
Luminous efficacy	97 lm/W
CCT	3000 K
CRI	90


LOR	100%
Total flux	1950 lm
Total power	20.1 W



1 x LED

Nominal lamp power	22.2 W
Lamp flux	2110 lm
Luminous efficacy	95 lm/W
CCT	3000 K
CRI	90


LOR	100%
Total flux	2110 lm
Total power	22.2 W



1 x LED

Nominal lamp power	24.5 W
Lamp flux	2260 lm
Luminous efficacy	92 lm/W
CCT	3000 K
CRI	90


LOR	100%
Total flux	2260 lm
Total power	24.5 W



1 x LED

Nominal lamp power	15.9 W
Lamp flux	1610 lm
Luminous efficacy	101 lm/W
CCT	3000 K
CRI	90


LOR	100%
Total flux	1610 lm
Total power	15.9 W



1 x LED


Nominal lamp power	11.8 W
Lamp flux	1250 lm
Luminous efficacy	106 lm/W
CCT	3000 K
CRI	90

LOR	100%
Total flux	1250 lm
Total power	11.8 W

**1 x LED**


Nominal lamp power	26.2 W
Lamp flux	2460 lm
Luminous efficacy	94 lm/W
CCT	3000 K
CRI	90

LOR	100%
Total flux	2460 lm
Total power	26.2 W

**1 x LED**


Nominal lamp power	35.1 W
Lamp flux	3060 lm
Luminous efficacy	87 lm/W
CCT	3000 K
CRI	90

LOR	100%
Total flux	3060 lm
Total power	35.1 W

**1 x LED**


Nominal lamp power	28.4 W
Lamp flux	2620 lm
Luminous efficacy	92 lm/W
CCT	3000 K
CRI	90

LOR	100%
Total flux	2620 lm
Total power	28.4 W

**1 x LED**


Nominal lamp power	30.6 W
Lamp flux	2770 lm
Luminous efficacy	91 lm/W
CCT	3000 K
CRI	90

LOR	100%
Total flux	2770 lm
Total power	30.6 W

**1 x LED**


Nominal lamp power	32.8 W
Lamp flux	2920 lm
Luminous efficacy	89 lm/W
CCT	3000 K
CRI	90

LOR	100%
Total flux	2920 lm
Total power	32.8 W




1 x LED

Nominal lamp power	37.4 W	LOR	100%
Lamp flux	3210 lm	Total flux	3210 lm
Luminous efficacy	86 lm/W	Total power	37.4 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	39.6 W	LOR	100%
Lamp flux	3350 lm	Total flux	3350 lm
Luminous efficacy	85 lm/W	Total power	39.6 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	44.5 W	LOR	100%
Lamp flux	3620 lm	Total flux	3620 lm
Luminous efficacy	81 lm/W	Total power	44.5 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	9.6 W	LOR	100%
Lamp flux	1050 lm	Total flux	1050 lm
Luminous efficacy	109 lm/W	Total power	9.6 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.28 in

Width: 7.28 in

Height: 4.53 in

Adjustability

Tiltable

Electric

System power: 9.6-44.5 W

Appliance Class: II

Protection

IP: 20