

Product data sheet

MACARON 1 POST TOP LUMINAIRES


MC-20001-T2-W40

LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 25,000 - Life time L80B10 Ta 50° 50,000 - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - High-efficiency PMMA lens - Durable silicone rubber gasket - Clear toughened glass lens

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	80.9 W	CRI	80
Total flux	7265 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	80.9 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 19.69 in
Diameter: 19.69 in
Weight: 10 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 80.9 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C