Product data sheet


PH 3/2 WALL E14 LED 2700K 5W 5743142806

LOUIS POULSEN



PH 3/2 Wall Design : Poul Henningsen Concept : The fixture is designed based on the principle of a reflective three-shade system, which directs the majority of the light downwards. The shades are made of mouth-blown opal three-layer glass, which is shiny on the top and sandblasted matt on the inside, giving a soft and diffuse light distribution. Finish : White opal glass. High lustre chrome plated. Material : Shades: Mouthblown white opal glass. Top plate: High lustre chrome plated, spun brass. Wall box: High lustre chrome plated, spun brass. Arm: High lustre chrome plated, brass. Mounting : Cable length: 2.9m. Light control: On wall plate. Class : Ingress protection IP20. Electric shock protection II w/o ground. Weight : Max. 2.5kg.

Light output 1



1 x LED Nominal lamp power

Lamp flux	
Luminous efficacy	
CCT	
CRI	

IP 20

5 W 470 lm 58 lm/W 2700 K 80

ULOR Total flux Total power

LOR

62%
16%
292 lm
5 W

Electric
System power: 5 W
Protection
15.00
IP: 20

Adjustability

Height: 9.25 in Diameter: 11.42 in

Mounting mode Wall mounted

Shape and measurements

Fixed