
# Product data sheet

PH 4½ - 3½ GLASS FLOOR E27 LED 2700K 15W 5744161514


LOUIS POULSEN





PH 4½-3½ Glass Floor Design : Poul Henningsen Concept : The fixture is designed based on the principle of a reflective three-shade system, which directs the majority of the light downwards. The shades are made of hand-blown opal three-layer glass, which is glossy on top and sandblasted matte on the underside, giving a soft and diffuse light distribution. Finish : High lustre chrome plated. White opal glass. Material : Shades: Mouth-blown white opal glass. Anti glare ring: Purple, spun aluminium. Top plate: High lustre chrome plated, spun brass. Base: High lustre chrome plated, spun brass. Stem: High lustre chrome plated, steel. Mounting : Cable type: Plastic cord with plug. Cable length: 3.3m. Light control: On/off switch on cord. Class : Ingress protection IP20. Electric shock protection II w/o ground. Weight : Max. 15kg.

Light output 1



1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI

15 W 1560 lm 57 lm/W 2700 K 80

LOR

LOR	55%
ULOR	15%
Total flux	861 lm
Total power	15 W

55%

## Mounting mode

Standing / Bollard

#### Shape and measurements

Height: 11.81 in Diameter: 17.72 in Weight: 0.2 kg

### Adjustability

Fixed

## Electric

System power: 15 W Appliance Class: II

### Protection

IP: 20 Designation labels: CE