

Product data sheet


URBANO LED 103W 12400LM 4000K IP66 O7 - FOR AREA LIGHTING REGULATION 0° ... +15° (O1, O2, O3, O4, O5, O7, O8 OP.. 130195.5L05.17

LUG



Professional streetlight luminaire for LED light sources. Mounting: on pillar $\varnothing 60/76\text{mm}$, on pillar $\varnothing 60/48\text{mm}$ (only for luminaires with a degree of regulation $0^\circ \dots +15^\circ$) - modification .834, on outriggers $\varnothing 60/76\text{mm}$, on outriggers $\varnothing 60/48\text{mm}$ (only for luminaires with a degree of regulation $0^\circ \dots +15^\circ$) - modification .834 Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.049 m^2 Power: 220-240V 50/60Hz Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, twilight sensor, 10kV surge protection, NTC Additional information: Tilt adjustment: 5° , knife switch (for protection class I), access to the driver chamber without the use of tools. The possibility of using one or more power supplies in the luminaire. Additional equipment: luminaire with holder for mounting on a $\varnothing 60/48\text{mm}$ pillar (only for luminaires with a degree of regulation $0^\circ \dots +15^\circ$) - index extension: .834 Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: freeways, express roads, local roads, town roads, residential area roads, area lighting Type of optics: O7 - for area lighting

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	103 W	CRI	274
Total flux	12400 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	103 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 28.74 in

Width: 11.61 in

Height: 5.31 in

Adjustability

Tiltable

Design

Color of housing: Anthracite / graphite

Electric

System power: 103 W

Appliance Class: I

Protection

IP: 66

IK: 09