



# Product data sheet

ECLPARIPMFC  
ECLPARIPMFC\_GREEN\_MEDIUM LENS  
PROLIGHTS



EclPar IPMFC is a flexible IP rated single source LED spotlight, featuring an 100W RGB+WarmWhite light source with high efficiency and advanced colour control. Its Spektra calibrated LED source delivers a high-quality white reproduction with high CRI and TM30 with an advanced control over colours, ensuring consistency across fixtures. The unit is compact and completely fan free, making the EclPar IPMFC a workhorse for any outdoor and dusty environment, but as well as for corporate and studio whereas silent operations are required. The flexible optical system allow a wide selection of lenses from narrow 15° (on board), flood 30°, and ultra wide 60°, which can be quickly mounted in front of the luminaire or inside the front tempered glass for lasting exterior installation. Features: 100W Spektra calibrated RGB + Warm White LED delivering high CRI, TLCI, TM30 values Flex lens system: 15° on-board - 30° and 60° optional IP65 for exterior application, fan free

## Light output 1



1 x LED			
Nominal lamp power	31.1 W	LOR	100%
Lamp flux	1158 lm	Total flux	1160 lm
Luminous efficacy	37 lm/W	Total power	31.1 W
CCT	0 K		
CRI	-18		

## Mounting mode

Ceiling mounted, Standing / Bollard

## Shape and measurements

Length: 10.19 in  
Width: 2.56 in  
Height: 9.74 in

## Adjustability

Rotatable, Tilttable, Free

## Design

Material impression: Aluminum

## Electric

System power: 31.1 W  
Controller: DMX  
Color adjustable  
Appliance Class: I

## Protection

IP: 65  
IK: 08  
Surface temperature: 50°C  
Designation labels: CE