


Product data sheet

PLANOS LED LICHTBAND
672256.002.07
RZB




IP
20

IK
03

Item Number: 672256.002.07 Series: Planos Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 Hz LED continuous line luminaire with three-row lens system. LED cover provided by plastic (PMMA) panel with integrated three-row lens system. With 5-pin connecting terminal as standard. LED drivers are suitable for emergency lighting systems in accordance with IEC60598-2-22 Medium beam light distribution. Single battery system with integrated self-test and feedback through Dali bus to RZB monitoring system 985405 only, including LED. Available Colours: white Type of Installation: modular elements Dimensions: L 1500, B 70, H 51mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: DALI-Sibe Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 7550lm System power: 52W Beam Angle: 106°/109° Number of fittings B10A: 24 Number of fittings B16A: 15 Number of fittings C10A: 24 Number of fittings C16A: 40 Inrush current: 19A Unified Glare Ratio: 23,5 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	62 W	CRI	80
Total flux	7550 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	62 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.76 in
Width: 59.06 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 62 W

Protection

IP: 20
IK: 03