


# Product data sheet

TRAFFIK R LED 53W 6550LM 3000K IP66 O32 - FOR PARKS AND PARKING LOTS GRAY I  
130292.5L071.051  
LUG



Professional streetlight luminaire for LED light sources. Mounting: on outriggers  $\varnothing 60/48\text{mm}$ , on pillar  $\varnothing 60/48\text{mm}$  Body: high pressure die-cast aluminum Lateral Surface Wind Exposed:  $0.033\text{ m}^2$  Power: 220-240V 50/60Hz Available on request: DIM 1..10V, LLOC, twilight sensor, 10kV surge protection, NTC Additional information: Tilt adjustment:  $-10^\circ$  to  $90^\circ$  (every  $5^\circ$ ) Other remarks: the pole and boom are not part of the luminaire; luminaire available in protection class I and II Warranty: 5 years Application: local roads, express roads, town roads, residential area roads, area lighting, avenues, promenade, parking areas Type of optics: O32 - for parks and parking lots

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 53 W     | CRI         | 70     |
| Total flux         | 6550 lm  | LOR         | 100%   |
| Luminous efficacy  | 124 lm/W | Total power | 53 W   |

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 24.21 in  
Width: 9.06 in  
Height: 3.15 in

## Adjustability

Tiltable

## Design

Color of housing: Silver gray

## Electric

System power: 53 W  
Appliance Class: I

## Protection

IP: 66  
IK: 08