Product data sheet

URBINI LED 36W 3800LM 3000K IP66 09 - FOR BIKE PATHS GRAY I 130232.5L281.101

LUG










Professional streetlight luminaire for LED light sources. Mounting: on pillar ø60mm, on horizontal and vertical pillars, on outriggers ø60mm, with mounting bracket (included) Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0,029 m² Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, NTC, LLOC, 10kV surge protection Additional equipment: additional anti-corrosive protection (index extension: .985) Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: cycle paths, avenues, sidewalks, parks, parking areas, residential, public spaces, playgrounds, promenade, residential area roads Type of optics: 09 - for bike paths

Light output 1 (integrated)



Lamp type	LED	
Nominal lamp power	36 W	
Total flux	3800 lm	
Luminous efficacy	106 lm/W	

Mounting mode

Pole top mounted

Shape and measurements

Length: 16.02 in Width: 4.33 in Height: 4.72 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 36 W Appliance Class: I CCT CRI

LOR

Total power

Protection

IP: 66 IK: 08 3000 K

70 100%

36 W