Product data sheet


BARIS 52 LED P SM 595MM 850LM 830 IP44 I KL. DALI PLX BIALY 9W
928888
LENA LIGHTING



IP 20 IK 03

928888 BARIS 52 LED P SM 595mm 850lm 830 IP44 I kl. DALI PLX BIALY 9W A recessed luminaire with classic proportions and modern design, intended for installation in modular ceilings. The luminaire is available in three lengths: 595mm, 1195mm, 1795mm. The housing of the luminaire is made of an anodized aluminum profile in gray or an aluminum profile painted in white or black (other colors available on request). The optical system is in the form of a dedicated, flexible opal diffuser that evenly illuminates the luminaire, with a PRM prismatic diffuser. The luminaire is equipped with a complete mounting system enabling quick and easy installation in modular ceilings.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	850 lm	LOR	100%
Luminous efficacy	94 lm/W	Total power	9 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 2.05 in
Height: 2.76 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 9 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: 77...95°F