


Product data sheet

FLAT POLYMERO KREIS
672125.002.3
RZB



IP
40

IK
03

Item Number: 672125.002.3 Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Self-contained system, standard with automatic self-test. Status indicator placed on the luminaire. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, , H 102mm Lamp: LED + LED 1.5 W Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) System power: 35W Beam Angle: 123° Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 20A Unified Glare Ratio: 20,3 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	37.1 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	98 lm/W	ULOR	15%
		Total power	37.1 W

Mounting mode

Wall mounted

Electric

System power: 37.1 W

Shape and measurements

Height: 3.86 in
Diameter: 20.28 in

Protection

IP: 40
IK: 03

Adjustability

Fixed