
Product data sheet

KOMBIC 150 RD 3700 IP43 840 WFL BK/BK
K21RD3540WF840NBB
LAMP



Round recessed downlight model KOMBIC 150 RD by Lamp brand. Reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Interior reflector and frame in black finish. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K with CR80. Luminaire with electronic wiring included. Insolation Class II. Lifetime: 100.000 L90 B10. With IP43 degree of protection. Group 0 photobiological safety. With Wide Flood optics to achieve a controlled light distribution and low UGR<19. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	19 W	LOR	100%
Lamp flux	2446 lm	Total flux	2443 lm
Luminous efficacy	129 lm/W	Total power	19 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in
Diameter: 5.91 in

Adjustability

Fixed

Electric

System power: 19 W
Appliance Class: II

Protection

IP: 40