
Product data sheet


SINUS SURFACE WHITE PRISM. 1910MM
R33A191-9016E1940L3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


low output LED 4000K CRI 90 74,6W 9498lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,4% https://katalog.planlicht.com/en-gb/fam-sinus/

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	9.32 W	CRI	90
Total flux	1187 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	9.32 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	9.32 W	CRI	90
Total flux	1187 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	9.32 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	9.32 W	CRI	90
Total flux	1187 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	9.32 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	9.32 W	CRI	90
Total flux	1187 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	9.32 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	9.32 W	CRI	90
Total flux	1187 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	9.32 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	9.32 W	CRI	90
Total flux	1187 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	9.32 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9.32 W	CRI	90
Total flux	1187 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	9.32 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9.32 W	CRI	90
Total flux	1187 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	9.32 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 75.20 in
Width: 75.20 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 74.6 W

Protection

IP: 40