



Product data sheet

LOUI 50
925343.002.1
RZB



Series: LESS IS MORE 50 system Gerades Modulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Nur optional: Lichtbandsystem vorbereitet für Seilabhngung! Colour: traffic white, matt (RAL 9016) Length: 1121 mm Width: 57 mm Height: 75 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 28 W Rated luminous flux: 3550 lm Luminous efficiency: 127 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	80
Total flux	3550 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	28 W

Mounting mode

Ceiling mounted

Electric

System power: 28 W

Shape and measurements

Length: 2.24 m
Width: 44.13 mm
Height: 2.95 mm

Protection

IP: 20
IK: 03

Adjustability

Fixed