




Product data sheet

PANELTECH HE R2 - UGR<LT/>19 - DIP SWITCH 4000K CRI 80 26W CLD WHITE
22185207-00
DISANO



Housing: body in steel sheet and frame in aluminium. Diffuser: extruded panel in high transmittance prismatic technopolymer. Internal PMMA slab. : UGR<lt/>19, according to standard EN 12464. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: Ceiling lighting fixture with external driver; it can be easily housed in false ceilings. Mounting: recessed only for surface mounting on T-beams or suspended. Easy installation: quick connection without the need to open the luminaire, can be easily inserted into the ceiling.

Light output 1



1 x LED			
Nominal lamp power	26 W	LOR	100%
Lamp flux	3566 lm	Total flux	3566 lm
Luminous efficacy	137 lm/W	Total power	26 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in
Width: 11.61 in
Height: 0.51 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 26 W
Appliance Class: II

Protection

IP: 40
IK: 05
Designation labels: CE