

Product data sheet

3-PH TRACK LIGHT FOCUSABLE, 35W, 30°-50°, BLACK MATT, 3000K, CRI92


114132

ISOLED



3-PH Track light focusable, 35W, 30°-50°, black matt, 3000K, CRI92 | Dimensioned wattage: 35 W | Effective wattage: 38.9 W | Energy efficiency class: E (EU 2019/2015) | Nominal Voltage: 220 - 240 V AC | Material: cast aluminum | Surface color: black matt | Protection class: IP20 | suitable for indoor use only | permissible ambient Temperatures: -20° - 40° C | Diameter: 98 mm | beam angle: 30° - 50° min-max | variably adjustable | color temperature: 3000K | Color rendering index: 92 (Ra 1-8) | Luminous flux: 4100 lm | Useful life: 68000 h (L80|B50) | Guarantee: 5 years | Special features: incl. 3-PH EURO adapter, passively cooled, incl. variable adjustment of the beam angle from 30° to 50°, dimensions of luminaire head: 106x135mm, | FABRICATION: ISOLED 114132

Light output 1



1 x LED

Nominal lamp power	38.9 W	LOR	100%
Lamp flux	4100 lm	Total flux	4101 lm
Luminous efficacy	105 lm/W	Total power	38.9 W
CCT	3000 K		
CRI	92		

Mounting mode

Ceiling mounted, Contact rail, Contact rail

Shape and measurements

Length: 5.91 in

Width: 3.94 in

Height: 7.48 in

Adjustability

Rotatable, Tilttable

Design

Material impression: Aluminum

Color of housing: Black

Electric

System power: 38.9 W

Ballast: ECG

Protection

IP: 20

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F