

Product data sheet

ARENO
501035.004
RZB



Series: Areno Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: die-cast aluminium, powder-coated. With three M20x1.5 cable inlets. Diffuser: textured glass, white coated inside. "Cover ring: die-cast aluminium, screw mounted; screw-on feet" inside. With silicone sealing ring. LEDs included. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 227, B 141, H 87 Lamp: LED Life time: 32000 h (L70/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 430lm System power: 18W Beam Angle: 142°/126° Unified Glare Ratio: 21,5 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18 W	CRI	80
Total flux	430 lm	LOR	100%
Luminous efficacy	24 lm/W	ULOR	13%
		Total power	18 W

Mounting mode

Wall mounted

Shape and measurements

Length: 5.55 in
Width: 8.94 in
Height: 3.35 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 65
IK: 03