


Product data sheet

NLED5601AE1 5W 3000K 24°单头格栅射灯(椭圆)
70092173
NVC



产品描述：光源类型：SMALITE LED SMD 驱动电源：内置一体恒流驱动 灯体材质：铝合金+塑料 面环颜色：99半光白 系列可选：NLED560A（常规款）/NLED560AE（椭圆款）单灯头数：单头（NLED5601）/双头（NLED5602）光束角：24°色温：3000K/4000K/5700K 显指：Ra80 功率：5W/9W/15W/20W 功率因数PF：0.50/0.95 光通量：375 lm/750 lm（5W单头/双头）；603 lm/1206 lm（9W单头/双头）；1060 /1150 lm（15W单头）；2120 /2300 lm（15W双头）；1200 /1300 lm（20W单头）；2400 /2600 lm（20W双头）。更新说明：暂无更新，敬请期待。

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.86 W	CRI	80
Total flux	375 lm	LOR	100%
Luminous efficacy	77 lm/W	Total power	4.86 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.33 in
Width: 4.33 in
Height: 1.97 in
Weight: 0.096 kg

Adjustability

Free

Electric

System power: 4.86 W
Appliance Class: II

Protection

IP: 20
IK: 04