

Product data sheet

DEECOS P MAXI
911480.002.1
RZB




IP
20

IK
06

Series: Deecos Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Ceiling canopy made of powder-coated sheet steel with magnetic attachment. Transparent pendant cable 2000 mm, can be shortened, with integrated steel cable. Housing: powder coated die cast aluminium. Heat-resistant plastic ring. Reflector material: MIRO-SILVER with 98% total light reflection, can be changed without tools. Lamp (LED) included. LED converter included. Available Colours: Traffic white, matt (RAL 9016) Type of Installation: Pendant Dimensions: D 123, H 181 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 4250lm System power: 37W Beam Angle: 34° Number of fittings B10A: 15 Number of fittings B16A: 24 Number of fittings C10A: 24 Number of fittings C16A: 40 Inrush current: 22A Unified Glare Ratio: 15,2 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	38 W

Mounting mode

Wall mounted

Electric

System power: 38 W

Shape and measurements

Height: 7.13 in
Diameter: 4.84 in

Protection

IP: 20
IK: 06

Adjustability

Fixed

Design

Color of housing: White