

Product data sheet


LED DIMMABLE ROUND SURFACE PANEL 24W 6500K
SRPL-24T/DIM
MPE



IP
20

- Round shape - Surface - mounted on ceiling - Light frame made of anti-oxidation aluminum alloy - Light guide plate made of PMMA plastic for uniform light distribution - Detachable driver for easy connection, Integrated driver EMC. - Use with Dimmer LED to adjust brightness - Size: Ø300 x 35 mm - Voltage: 100-240VAC - Power: 24W - Power Factor (PF): >0.5 - Luminance: 1800 lm - Color Temperature (CCT): 6000-6500K - RA >80 High Color Rendering Index - Beam angle: 120° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s - European Standard CE - RoHS

Light output 1



1 x LED			
Nominal lamp power	24 W	LOR	102%
Lamp flux	1800 lm	Total flux	1830 lm
Luminous efficacy	76 lm/W	Total power	24 W
CCT	6500 K		
CRI	82		

Mounting mode

Ceiling mounted

Electric

System power: 24 W

Shape and measurements

Length: 11.81 in

Width: 11.81 in

Height: 1.26 in

Protection

IP: 20

Adjustability

Fixed