


# Product data sheet


LEDSPANELRC-SL SQ595-40W-6500-WH IV  
542004059210  
OPPLE



IP  
20

Housing: Aluminum+PMMA; Mounting ring: white; Installation: recessed, surface mounted, suspend;(need corresponding accessories)  
Dimensions: 595×595×9mm; Ceiling cutouts: 585×585mm; Beam angle: 120°; Lamp(s): LED; Power: 40W; Efficacy : 100Lm/w; Total luminous flux of luminaire: 4000lm; Power Factor: 0.95; Mains voltage: 220-240V/50-60Hz; Colour temperature: 6500K; Colour rendering: Ra80; UGR: 22; IP/IK Grade: IP20/IP44(IP44 only front); Class of protection II; Control System: on/off Service life: 30,000h at 70% luminous flux;

## Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	40 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	40 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.43 in

Width: 23.43 in

Height: 0.35 in

## Adjustability

Fixed

## Electric

System power: 40 W

## Protection

IP: 20