Product data sheet


MINI SPACE
2040-B-3-904-XX
UNILAMP



IP 66 IK 09

SPACE Space is a range of next generation flood lights for demanding outdoor lighting tasks. Six different tailored made light engines cover a wide range of lighting applications. High efficacy 3SDCM COBs offer highest lumen output. The high power LED options for SPACE gives lighting designers a wide choice of carefully calculated light distributions, including an ultra-narrow beam down to 6°. The SPACE RGBW version with optics-based color mixing is the ideal solution for impactful highlighting of outdoor spaces. SPACE cans also be customized to tunable white solution which allows tasteful illumination of architectural structures in different color temperatures. Regardless of LED option, a glare shield cap, snoot and luminaire integrated honeycombs are available as standard accessory. Different mounting solutions such as a pole clamp or pole arm let SPACE to be installed in numerous applications. SPACE can be equipped with a built-in photocell, DALI2 control system or state of the art wireless control utilizing CASAMBI. Minimal amount of tools required for installation and the prewired electrical connection simplifies the installation process. Features: • Same look and feel across the range • Various light distributions and LED options to choose from • Supreme surge protection: mains and dimming line 10kV protected • High ambient temperature rating up to 50°C • Computer optimized housing structure, ultra-robust yet light weight

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	5040 lm	ULOR	7%
Luminous efficacy	168 lm/W	Total flux	5040 lm
CCT	4000 K	Total power	33 W
CRI	80		

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 3.01 in
Width: 6.52 in
Height: 4.31 in

Adjustability

Free

Electric

System power: 33 W
Appliance Class: I

Protection

IP: 66
IK: 09