


Product data sheet

VIGILANT LED LOW BAY 18000 LUMENS, ULTRA WIDE DISTRIBUTION, DIFFUSED POLYCARBONATE DOME LENS
 LWELUC2CDANNGN
 DIALIGHT



Vigilant LED Low Bay 18,000 Lumens 154 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Diffused Polycarbonate Dome Lens CE, ENEC EN 60598:2015 EN60598-2-1 (ed.1), IEC 60598-2-1 (ed.8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN62493:2010 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-2 IK10 Ultra Wide Distribution IP66/67 Scaled IES File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	154 W	CRI	80
Total flux	18001 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	154 W

Mounting mode

Pendant

Shape and measurements

Length: 15.94 in

Width: 15.94 in

Height: 8.27 in

Adjustability

Rotatable, Tilttable

Electric

System power: 154 W

Appliance Class: I

Protection

IP: 66

IK: 10

Other operating numbers

Ambient temperature range: -40...149°F