Product data sheet

LINEDO_2,3M_60_1111
952360.850.776.001
RZB



IP 54 IK 03

LINEDO, 60 W, 9750 lm, 850, aluminium, DALI Continuous line luminaire, L 2291 B 58 H 76

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	15 W	CRI	80
Total flux	2438 lm	LOR	100%
Luminous efficacy	163 lm/W	Total power	15 W

Light output 2 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	15 W	CRI	80
Total flux	2438 lm	LOR	100%
Luminous efficacy	163 lm/W	Total power	15 W

Light output 3 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	15 W	CRI	80
Total flux	2438 lm	LOR	100%
Luminous efficacy	163 lm/W	Total power	15 W

Light output 4 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	15 W	CRI	80
Total flux	2438 lm	LOR	100%
Luminous efficacy	163 lm/W	Total power	15 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 90.20 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 60 W

Protection

IP: 54
IK: 03