Product data sheet

LUCAS VIII (WALL FITTING) 9.828.2152.15

LEIPZIGER LEUCHTEN







Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz

Light output 1



1 x High pressure sodium	vapour lamp		
Nominal lamp power	50 W	LOR	80%
Lamp flux	3500 lm	ULOR	4%
Luminous efficacy	45 lm/W	Total flux	2788 lm
CCT	2000 K	Total power	62 W
CRI	25		



i x High pressure sodium vapour lamp				
Nominal lamp power	70 W	LOR	80%	
Lamp flux	5600 lm	ULOR	4%	
Luminous efficacy	54 lm/W	Total flux	4461 lm	
CCT	2000 K	Total power	83 W	
CRI	25			

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 62-83 W

Protection

IP: 55