


Product data sheet

SCAPHA
311992.004.76
RZB



Series: SCAPHA Pendant luminaire with elliptical shape. Base: aluminium, powder-coated. Canopy and glass fixture steel powder-coated. Handmade concave glass, matt finish on the outside, painted white on the inside. Uniform and glare-free illumination of the small boat shaped corpus by specially adapted LED panel boards. Suitable for pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request. TouchDim sensor capable. Light and/or presence sensors can be integrated. Colour: silver, metallic Length: 1264 mm Width: 174 mm Height: 66.5 mm Suspension length: 500-1200 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 51 W Rated luminous flux: 3400 lm Luminous efficiency: 67 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	51 W	CRI	80
Total flux	3400 lm	LOR	100%
Luminous efficacy	67 lm/W	ULOR	11%
		Total power	51 W

Mounting mode

Pendant

Shape and measurements

Length: 6.85 in
Width: 49.76 in
Height: 2.64 in

Adjustability

Fixed

Design

Material impression: Matt, Plastic
Color of housing: White

Electric

System power: 51 W
Ballast: ECG

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 20
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F