Product data sheet

3878 CHANNEL - DIRECT AND INDIRECT LIGHT 4000K CRI 80 67W CLD WHITE
145182-00
DISANO



IP 20 IK 07

Housing: in extruded aluminium with die-cast aluminium end caps. Optics: dark light double parabolic louvers in high gloss 99.99 aluminium, anti-dazzle and anti-iridescent, very low luminance, and PDV treatment. : UGR<lt/>19, according to standard EN 12464. Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: snap-fastened optics, it stays attached with fall-proof springs.

Light output 1



1 x LED

Nominal lamp power	67 W	LOR	100%
Lamp flux	6943 lm	Total flux	6942 lm
Luminous efficacy	104 lm/W	Total power	67 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 58.27 in
Width: 8.27 in
Height: 2.40 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 67 W
Appliance Class: I

Protection

IP: 20
IK: 07
Designation labels: CE