Product data sheet

CENTRYXX W IP65
672305.002.89
RZB



IP 65 IK 08

Item Number: 672305.002.89 Series: Centryxx IP Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Cover: plastic (polycarbonate). Bracket die-cast aluminium,powder-coated. LED lamp insert with clear plastic lenses for escape route illumination. Swivels vertically. Integrated converter. With AC Control monitoring module for Luxifaircentral battery units. Lamp (LED) included. Available Colours: white Type of Installation: Wall (surface) Dimensions: L 79, B 198, H 198mm Lamp: LED Colour Temperature: 6500K Socket 1: without socket Operating Mode Lamp 1: EB Emergency Lighting System: AC-Control Safety Marks: F-mark Impact Protection: IK08 (5 Joule) Luminaire flux LED: 160lm System power: 4,2W Beam Angle: 90°/0°/90°/90° Number of fittings B10A: 9 Number of fittings B16A: 15 Number of fittings C10A: 15 Number of fittings C16A: 24 Inrush current: 16A Unified Glare Ratio: 38,2 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	4.2 W	CRI	70
Total flux	160 lm	LOR	100%
Luminous efficacy	38 lm/W	ULOR	21%
		Total power	4.2 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 7.80 in
Width: 7.80 in
Height: 3.07 in

Adjustability

Fixed

Electric

System power: 4.2 W

Protection

IP: 65
IK: 08