


# Product data sheet

URBANO LED PLUS VERSION 302W 44150LM 4000K IP66 O70 - FOR TOWN AND LOCAL ROADS GRAY I TILT ADJUSTMEN..  
130192.3L60.130  
LUG



Professional streetlight luminaire for LED light sources. Mounting: on pillar  $\varnothing 60/76$ mm, on outriggers  $\varnothing 60/76$ mm Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.050 m<sup>2</sup> Power supply efficiency >93% Power: 220-240V 50/60Hz Lifetime LED (L90): 100 000 h Available on request: DIM 1..10V, LLOC, twilight sensor, 10kV surge protection Additional information: Tilt adjustment: 5°, knife switch (for protection class I), access to the driver chamber without the use of tools, NTC. The possibility of using one or more power supplies in the luminaire. CRI/Ra >70 Additional equipment: additional anti-corrosive protection (index extension: .985) Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: freeways, express roads, local roads, town roads, residential area roads, area lighting, airports, parking areas. Type of optics: O70 - for town and local roads

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	302 W	CRI	70
Total flux	44150 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	302 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 35.04 in

Width: 15.35 in

Height: 4.37 in

## Adjustability

Tiltable

## Design

Color of housing: Silver gray

## Electric

System power: 302 W

Controller: DALI

Appliance Class: I

## Protection

IP: 66

IK: 08