


Product data sheet

NLED5821C 1×12W 24°3500K 单头通用型格栅射灯
70075597
NVC



产品描述：光源类型：优质COB芯片 驱动电源：外置隔离式恒流驱动 灯体材质：铝合金 面环颜色：半光白（70075597）、亮光银灰（70075621）表面处理：喷涂（亮光银灰）安装方式：嵌入式 投射调节：可调节（水平MAX ±35°，垂直MAX + 30°）系列可选：单灯头数：单头/双头/三头 光通（lm）：350/380/400/400（1×6W）；450/480/500/500（1×9W）；650/670/700/700（1×12W）；1350/1440/1500/1500（1×20W）。光束（°）：15/24 色温（K）：3000/3500/4000/5700 显指（Ra）：80 功率（W）：1×6/2×6/3×6（NLED582*A）；1×9/2×9/3×9（NLED582*B）；1×12/2×12/3×12（NLED582*C）；1×20/2×20/3×20（NLED582*D）。功率因数PF：0.80（NLED582*A）；0.90（NLED582*B、NLED582*C、NLED582*D）。更新说明：暂无更新，敬请期待。更多信息：暂无链接，敬请期待。

Light output 1 (integrated)



Lamp type	LED	CCT	3500 K
Nominal lamp power	12 W	CRI	80
Total flux	670 lm	LOR	100%
Luminous efficacy	56 lm/W	Total power	12 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.14 in

Width: 5.14 in

Height: 3.07 in

Adjustability

Rotatable, Free

Design

Material impression: Matt, Plastic

Color of housing: White

Electric

System power: 12 W

Ballast: ECG

Controller: DALI

Appliance Class: II

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 20

IK: 04

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 14...95°F