Product data sheet

LED DOWNLIGHTS
V1-R0-00137-20D01-2001830 DL-ROLL OPAL Ø140 SURFACE MOUNTED 18W 3000K DALI
VARTON



IP 20 IK 01

Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Protection class: II Housing material: Aluminium Mounting method: Surface mounting Ingress protection (IP): IP20 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/daunlayty/dl-roll/dl-roll-opal-140-nakladnye/svetodiodnyy-svetilnik-varton-dl-roll-18-vt-nakladnoy-3000-k-140kh190-mm-ral9003-belyy-muar-s-rassei_1/

Light output 1



1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1700 lm	Total flux	1700 lm
Luminous efficacy	94 lm/W	Total power	18 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.48 in
Diameter: 5.51 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 20
IK: 01