# Product data sheet


OUTDOOR LIGHTING
V1-S1-70760-40D05-6611040 LEVANTE YARD 110W 4000K DALI
VARTON



IP 66 IK 03

LED street light luminaire with a concise design. Adjustable spigot. Cast aluminum housing. Application: objects without illumination requirements. Installation: pole mounted and side-entry mounted (Ø40mm-48mm/Ø48mm-60mm). Power factor: 0,95 Ingress protection (IP): IP66 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Color rendering index: 70-79 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/levante/levante-yard-dlya-dvora/svetodiodnyy-svetilnik-varton-ulichnyy-levante-m-yard-110-vt-kronshteyn-60-mm-4000-k-ral7045-seryy-m_2/

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 110 W | LOR | 100% |
| Lamp flux | 14300 lm | Total flux | 14300 lm |
| Luminous efficacy | 130 lm/W | Total power | 110 W |
| CCT | 4000 K | | |
| CRI | 70 | | |

### Mounting mode

Pole integrated

### Shape and measurements

Length: 34.45 in
Width: 5.87 in
Height: 4.37 in

### Adjustability

Fixed

### Electric

System power: 110 W

### Protection

IP: 66
IK: 03