

Product data sheet

DEECOS S MINI TRACK-IN
742263.002.1.730
RZB




IP
20

IK
06

Series: DEECOS S mini track-in LED surface-mounted projector in modern design with no visible cooling ribs. Housing: die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling, Wall track. Track-in driver integrated into the adapter. High quality converter without flickering and stroboscopic effect. With Casambi smart+free Bluetooth control for wireless network and operation using Android / iOS devices, free app available for download. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: traffic white, matt (RAL 9016) Diameter: 87 mm Height: 135 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 92 System power: 29 W Rated luminous flux: 3000 lm Beam angle Down: 44° Luminous efficiency: 103 lm/W Control gear: Dimmable Bluetooth converter Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	29 W	CRI	90
Total flux	3000 lm	LOR	74%
Luminous efficacy	103 lm/W	ULOR	20%
		Total power	29 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.31 in
Diameter: 3.43 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: White

Electric

System power: 29 W

Protection

IP: 20
IK: 06