



Product data sheet

FLAT BASIC
211399.002.1.19
RZB



Series: FLAT BASIC Decorative round surface-mounted luminaire. Base: plastic. Triplex glass produces particularly homogeneous, soft and glare free lighting. Suitable for ceiling mounting, wall (surface). With integrated HF movement sensor. Functional parameters of a master luminaire (ceiling height of approx. 2.8m): HF detector 24GHz with integrated corridor function. Coverage: approx. 130° radial. Easy adjustment of functions via associated push button switches. Sensitivity/Range: 0.5-5m radial, adjustable from 10-100%. Time control 1second to 15minutes in 8different levels. Daylight detection with 5brightness levels and learning mode. Up to 9slave luminaires can be operated with one master luminaire (max. up to 150W / 230W). Suitable for outdoor use to a limited extent only, as it is sensitive to all movements. Colour: pure white (RAL9010) Diameter: 370mm Height: 118mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 83 System power: 12W Rated luminous flux: 1150lm Luminous efficiency: 96lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP43

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	12 W	CRI	80
Total flux	1150 lm	LOR	100%
Luminous efficacy	96 lm/W	ULOR	15%
		Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.65 in
Diameter: 14.57 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 43
IK: 02