

Product data sheet

FORMAT1 URBAN LIGHTING - 35W - 3350LM - TYPE VS-W
0884007A-840
ARCLUCE




IP
66

IK
09

IP DEGREE : IP66 IK RATING : IK09 ELECTRICAL INSULATION CLASS: II LUMINAIRE Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 5mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3. INSTALLATION Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	80
Total flux	3350 lm	LOR	100%
Luminous efficacy	96 lm/W	Total power	35 W

Mounting mode

Pole top mounted

Electric

System power: 35 W

Shape and measurements

Length: 20.47 in

Width: 9.84 in

Height: 3.74 in

Protection

IP: 66

IK: 09

Adjustability

Fixed