


Product data sheet

LUXCAN MICRO SEMI-RECESSED ROUND 600 15° EDD 04 827
19.4374.1163.04
LUXIONA



Indoor luminaire. Assembly: mounted in suspended ceiling. The body material is aluminum. Colour - RAL 9005 (black). Dimensions: Ø33 x 65 mm. Diffuser: optical system based on PMMA lenses. The efficiency of the optical system is 75,14%. Beam angle: (C0-C180) / (C90-C270) - 17,8° / 19,8°. Light source type: LED. Colour of the light 2700 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 489,6 lm. Power of luminaire: 5,4 W. Luminaire's light efficiency: 90,7 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Operating temperature range: 5 ÷ 35° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: III. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	5.4 W	LOR	52%
Lamp flux	621 lm	Total flux	326 lm
Luminous efficacy	115 lm/W	Total power	5.4 W
CCT	2700 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.56 in
Diameter: 1.30 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: Black

Electric

System power: 5.4 W
Controller: DALI
Appliance Class: III

Protection

IP: 20
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F