# Product data sheet


HAMILTON 2 STREET AND AREA LIGHTING LUMINAIRES
HAM-20011-M-W40
LIGMAN



IP 66 IK 07


- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear - Surge protection 10 kV

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 53.2 W | CRI | 80 |
| Total flux | 6996 lm | LOR | 100% |
| Luminous efficacy | 132 lm/W | ULOR | 50% |
| | | Total power | 53.2 W |

## Light output 2 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 53.2 W | CRI | 80 |
| Total flux | 6996 lm | LOR | 100% |
| Luminous efficacy | 132 lm/W | ULOR | 50% |
| | | Total power | 53.2 W |

### Mounting mode

Pole top mounted

### Shape and measurements

Height: 13.39 in
Diameter: 19.69 in
Weight: 29.74 kg

### Adjustability

Fixed

### Glare protection

Glare protection: UGR < 19

### Electric

System power: 106.4 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 66

IK: 07

Surface temperature: 40°C